

**In the Claims:**

Please cancel claims 1-8.

Please amend the following claims:

12. (amended) The actuator assembly according to claim 11, further comprising:

(a) a second indicator switch mounted to the rail, the position plate operable to engage the second switch as the actuator arm is moved, the second switch generating an electrical signal representative of soft ride firmness.

13. (amended) The actuator assembly according to claim 12, further comprising:

(a) a third indicator switch mounted to the rail, the position plate operable to engage the third switch as the actuator arm is moved, the third switch generating an electrical signal representative of hard ride firmness.

14. (twice amended) The actuator assembly according to claim 10 wherein a second ball bearing is located within the channel spaced apart from the first ball bearing, the second ball bearing having a second stud attached to the actuator arm.

B 17. (twice amended) An actuator assembly for moving an air valve between a first position in which air is admitted to an air bag mounted in a vehicle and a second position in which air is released from the air bag, the air valve pneumatically communicating with the air bag, the air valve having a rod in contact with an axle of the vehicle, the assembly comprising:

- a) a rail attached to a cross member of the vehicle;
- b) an actuator attached to the rail, the actuator having a movable shaft;
- c) an actuator arm attached to the rail and having a first end attached to the actuator, the actuator operable to linearly move the arm;
- d) a ball bearing movably retained within the rail, the ball bearing having a stud extending from the ball bearing through the actuator arm and attached to the actuator shaft; and
- e) a mounting plate having an end attached to the air valve and another end attached to a second end of the actuator arm, the actuator operable to move the air valve between the first and second positions so as to adjust the ride firmness of the vehicle.

Please add the following new claims:

*Beatz* 19. An assembly for allowing a vehicle operator to admit or release air to an air bag mounted in a vehicle, the vehicle having a frame and an axle, the assembly comprising:

- a) an actuator attached to the frame;
- b) an air valve pneumatically communicated with the air bag, the actuator connected to the air valve;
- C* c) a control switch connected to the actuator to allow the vehicle operator to control the actuator, the actuator operable to admit or release air from the air bag so as to adjust the ride firmness of the vehicle; and
- d) a rod connected to the air valve and extending from the air valve to the axle, the rod adapted to move the air valve to admit or release air from the air bag in response to the vehicle load changing.

*manual* →

*B  
cancel*

20. The assembly according to claim 19, wherein the control switch and the actuator operate independently of the rod to open or close the air valve.

21. The assembly according to claim 19, wherein an indicating device is mounted with the assembly to detect position.

*CI  
cancel*

22. The assembly according to claim 21, wherein the indicating device is an indicator switch mounted to the actuator.

23. The assembly according to claim 22, wherein the indicator switch is connected with a light that is viewable by the vehicle operator.

24. The assembly according to claim 19, wherein the air valve can be opened or closed by the operator while the vehicle is in motion.

*indicates*

### REMARKS

The following are applicant's response to issues raised in the Office Action.

Applicants respectfully request entry of this amendment in order to move the instant application toward allowance or alternatively, to place the application in better form for appeal.